



IRSEN45/042

High-frequency internal vibrators

Concrete consolidation with comfortable operation

The Wacker Neuson IRSEN series of high-frequency internal vibrators offer a short protection hose and low vibration handle. The ergonomically designed handle with vibration damping offers a high degree of comfort during operation. Wacker Neuson's IRSEN high-quality internal vibrators offer a variety of features and benefits.

Highlights

- Handle (Low Vib)
- High-performance electric motor with stable speeds
- Made in Germany
- Sturdy design

Technical Data

Electrical - Output Details		Weight	7.20 kg
Nominal current	10.00 A	Rubber cap	no
Nominal voltage	42.0 V	Motor	
Nominal frequency	200.0 Hz	Motor type	Asynchronous motor
Nominal power [P]	0.58 KW	Environment Data	
Phase	3.0 ~	Protection class	III / Safety extra-low voltage
Mechanical - Output Details		Degree of protection	IP67
Amplitude at air	2.300 mm	Electrical System	
Vibrations	12,000.0 1/min	Breaker Switch On/Off	Yes
Vibrations (Hz)	200.0 Hz	Integrated transformer	No
Mechanical Details		Length Cable	15.0 m
Length Hose	0.8 m	Kind of plug	CEE-Plug 3P 32A 42V 4H

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.