



## FUE10/042/200

### Stationary frequency converters

Safety and output for long-term application

When it comes to safety and high output during long-term application there is no compromise with these electronic frequency converters. Besides, they are very sturdy and maintenance-free. Their high-quality components and the all-round housing offer protection against shocks, impacts and water.

### Highlights

- Completely maintenance-free
- Secure protection

### Technical Data

#### ■ Electrical - Output Details

|                   |                 |
|-------------------|-----------------|
| Nominal current   | 24.50 A         |
| Nominal voltage   | 400.0 - 415.0 V |
| Nominal frequency | 50.0 - 60.0 Hz  |
| Output current    | 145.0 A         |
| Output voltage    | 42.0 V          |
| Output frequency  | 0.0 - 200.0 Hz  |
| Phase             | 3.0 ~           |
| Output Phase      | 3.0 ~           |

#### ■ Mechanical Details

|        |          |
|--------|----------|
| Length | 500.0 mm |
| Width  | 500.0 mm |

|        |          |
|--------|----------|
| Height | 550.0 mm |
| Weight | 87.00 kg |

#### ■ Environment Data

|                      |                         |
|----------------------|-------------------------|
| Protection class     | I / Protective earthing |
| Degree of protection | IP54                    |

#### ■ Electrical System

|                       |                         |
|-----------------------|-------------------------|
| Breaker Switch On/Off | Yes                     |
| Operating indicator   | yes                     |
| Adjusting frequency   | yes                     |
| Length Cable          | 2.5 m                   |
| Kind of plug          | CEE-Plug 5P 32A 400V 6H |