



IRSEN30/042

High-frequency internal vibrators

Concrete consolidation with comfortable operation

The Wacker Neuson IRSEN series of high-frequency internal vibrators offer a short protection hose and low vibration handle. The ergonomically designed handle with vibration damping offers a high degree of comfort during operation. Wacker Neuson's IRSEN high-quality internal vibrators offer a variety of features and benefits.

Highlights

- Handle (Low Vib)
- High-performance electric motor with stable speeds
- Made in Germany
- Sturdy design

Technical Data

Electrical - Output Details Weight 5.10 kg 3.50 A Nominal current Rubber cap no Nominal voltage 42.0 V Motor Nominal frequency 200.0 Hz Motor type Asynchronous motor Nominal power [P] 0.20 KW Environment Data 3.0 ~ Phase Protection class III / Safety extra-low voltage Mechanical - Output Details Degree of protection IP67 Amplitude at air 2.000 mm Electrical System Vibrations 12,000.0 1/min Breaker Switch On/Off Yes Vibrations (Hz) 200.0 Hz Integrated transformer No Mechanical Details Length Cable 15.0 m 0.8 m Length Hose CEE-Plug 3P 32A 42V 4H Kind of plug

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.