



FUE M/S 75A 6CEE-32A

Portable frequency converters

Light, sturdy and powerful

The frequency converters of the FUE series are distinguished by their light and compact design. Thanks to the aluminum design, they are easy to handle. With their high-quality electronics and the active cooling system, these machines deliver the highest output even in long-term application. The intelligent load and voltage management is particularly practical. It compensates for fluctuations of mains input voltage, incorrectly dimensioned extensions or appliances with greatly varying use of power.

Highlights

Intelligent load and voltage management

Technical Data

Electrical - Output Details

Electrical - Output Details		Weight	29.50 kg
Nominal current	13.00 A	Environment Data	
Nominal voltage	400.0 - 415.0 V	Protection class	I / Protective earthing
Nominal frequency	50.0 - 60.0 Hz	Degree of protection	IP44
Output current	75.0 A	Electrical System	
Output voltage	42.0 V	Breaker Switch On/Off	Yes
Output frequency	0.0 - 200.0 Hz	Operating indicator	yes
Phase	3.0 ~	Adjusting frequency	yes
Output Phase	3.0 ~	Length Cable	2.5 m
Mechanical Details		Kind of plug	CEE-Plug 5P 16A 400V 6H
Length	520.0 mm	Receptacle Type	CEE 3P 32A 4H 50V 100-200Hz
Width	310.0 mm	Number of Sockets	6.0
Height	494.0 mm		

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.